



www.wearwell.com

## 24/Seven LockSafe Nitrile Rubber (NBR) Corner - Case of 4, Yellow

### Group 578-CNBRYL

24/Seven LockSafe Nitrile Rubber (NBR) corners offer a secure connection with 24/Seven LockSafe NBR ramps and tiles. These separate corners alleviate the time, costs, and waste associated with traditional modular rubber edging that requires cutting.

- Nitrile Rubber (NBR)
- Ideal for oily, greasy, high-demand areas
- Optimum chemical resistance
- Case of 4
- 3" wide
- Overall thickness 5/8"
- Female and male edging available
- Available in black and yellow

**Wearwell Categories** Anti-Fatigue Flooring

**Suitable Environment** Dry, Wet, Oily, Slippery

**Customisation Level** C3 - Full Custom (Length, Width, Shape)

**Solid or Drainage** Solid

**Compound** Nitrile Rubber (NBR)

**Recycled** >50%

**Warranty** 1 Year

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	Federal Standard 191 Modified / 1% loss
Temperature Range	10 to 140 F
Coefficient of Friction	ASTM F1677 / Dry: COF = 1.04 / Wet COF = 0.94
Compression Deflection	Not Applicable
Tear Strength	Not Applicable
ESD Rating	Not Applicable
Dielectric Strength	Not Applicable

SKU	UPC	Colour	Thickness	Dimensions	Stock Part	UOM
-----	-----	--------	-----------	------------	------------	-----