



www.wearwell.com

## 24/Seven® LockSafe® Open ESD - Interlocking Floor Tiles 3' x 3'

### Group 772-GR

Static Electricity can produce damaging sparks that can ruin and destroy expensive equipment. 24/SEVEN LockSafe Open [ESD](#) eliminates static while providing a drainage ergonomic work surface for your team to perform. Made to cover large areas quickly, the 772 ESD can be placed directly atop a conductive coating or floor, eliminating the need for messy grounding cords. For more conventional installations, each tile comes with the grounding snap already installed for use with a grounding cord. The 'positive interlock' technology allows the rubber tiles to lock in while remaining easy enough to 'unzip' for reconfiguration. Around electronics keeping a work area clean is very important. The [LockSafe](#) connection system allows the mat to be rolled up to make keeping a cleaning easier.

NOTE: Unless used over a conductive floor, mats must be grounded with a ground cord ([793-Cord](#)) and users must wear a heel grounder ([793-Heel](#))

- U.S. PATENT NO. D882,293 S
- Tiles interlock securely and come apart on demand for reconfiguration
- EOS/ESD S7.1:  $1 \times 10^6 - 1 \times 10^9$  (meets ANSI/ESD 20.20 requirements)
- Cover large areas with drainage ESD dissipative ergonomic flooring in minutes

- Open grease resistant rubber best in lightly wet and slippery dry areas
- Grounding snap on each mat
- Safety ramps do not possess ESD properties
- 3' x 3' (91x91cm) rubber tiles
- Overall thickness 5/8" (15.9 mm)
- Unless used over a conductive floor, mats must be grounded with a ground cord (793-Cord) and users must wear a heel grounder (793-Heel)

Learn more about ESD flooring and matting in our blog - [ESD 101: Everything You Need to Know About ESD Mats, Flooring, and Work Surfaces](#).

**Wearwell Categories** Anti-Fatigue Flooring

**Suitable Environment** Dry, Wet, Slippery

**Customisation Level** C3 - Full Custom (Length, Width, Shape)

**Solid or Drainage** Drainage

**Compound** Grease Resistant Natural Rubber (GR)

**Recycled** >50%

**Warranty** 1 Year

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	Federal Standard 191 / 1% lost @ 1,000 cycles
Temperature Range	10 to 140 F
Coefficient of Friction	ASTM F1677 / Dry: COF = .90 / Wet COF = .020
Compression Deflection	Not Available
Tear Strength	Not Available
ESD Rating	EOS/ESD S7.1: $1 \times 10^6 - 1 \times 10^9$ (meets ANSI/ESD 20.20 requirements)

Dielectric Strength	Not Available
---------------------	---------------

SKU	UPC	Colour	Thickness	Dimensions	Stock Part	UOM
772.58x3x3GRBK	715411012022	Black		3' x 3'	Y	EA