



www.wearwell.com

## 24/Seven® LockSafe® Grade A® - Open Interlocking Rubber Floor Tiles

### Group 582

Grade "A" mats are designed to combat fatigue while **addressing specific issues unique to food and beverage production environments**. 3'x3' interlocking tiles have strong connections and are easy to lift and clean. The proprietary Nitrile compound passes NSF test ASTM G21-96 (2002), has GRAS status and is CFIA approved. Grade "A" gets an "A" for specialized food and beverage production applications. 'Positive interlock' allows the rubber tiles to lock in, while remaining easy enough to 'unzip' for reconfiguration.

For a workstation version of Grade A, check out our ["Grade A Workstation mat"](#)

- 100% anti-microbial rubber for food and beverage production and processing
- Meets the ASTM G21 standard for anti-microbial properties
- Knob style under structure for superior drainage and support
- Tiles interlock securely and come apart on demand for reconfiguration
- Cover large areas quickly with food processing ergonomic floor
- Color: Terra Cotta
- Overall thickness 1/2"
- 3'x 3' (91x91cm) rubber tiles
- U.S. PATENT No. D882,293 S

Learn more about 24/SEVEN LockSafe or find other 24/SEVEN LockSafe related products [here](#).

**Wearwell Categories** Anti-Fatigue Flooring

**Suitable Environment** Dry, Wet, Oily, Slippery

**Customisation Level** C3 - Full Custom (Length, Width, Shape)

**Solid or Drainage** Drainage

**Compound** Nitrile Rubber (NBR)

**Recycled** <10%

**Warranty** 1 Year

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	Federal Standard 191 Modified / 1% loss
Temperature Range	10 to 140 F
Coefficient of Friction	ASTM F1677 / Dry: COF = .9 / Wet COF = .7
Compression Deflection	Not Available
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Colour	Thickness	Dimensions	Stock Part	UOM
582.58x3x3TC		Terra Cotta	0.625	3' x 3'	Y	EA

