



www.wearwell.com

ErgoDeck MAX Diamond-Plate

Group 599W

Gone are the days of having to choose between comfort and customization. Introducing a modular tile that takes flexibility, performance and safety to the max - ErgoDeck MAX. ErgoDeck Max with patented LockSafe technology. holds secure but can be taken apart and reconnected on demand. This revolutionary product utilizes a universal edging system for simple configuration and installation. Each section features counter sunk holes for semi-permanent installations and traction bars for added slip prevention. ErgoDeck Max carries a Limited-Lifetime Warranty. US Patent No. 10,914,081

- U.S. PATENT NO. 10,914,081; 11,174,648; D502,557; D520,650
- Comfortable sponge base
- NFSI Certified
- Custom fit to any station or booth
- Easy to install, universal ramps
- Overall thickness 7/8" (22 mm)
- Made in the USA

Learn more about welding matting and flooring solutions [here](#).

Wearwell Categories Anti-Fatigue Flooring

Suitable Environment Dry

Customisation Level C3 - Full Custom (Length, Width, Shape)

Solid or Drainage Solid

Compound PVC/Nitrile Sponge

Recycled <30%

Warranty Lifetime

| Property | Test / Result |
|-------------------------|---|
| Flammability | MVSS 302 / 'A'; Rating |
| Taber Abrasion | ASTM D 3884 / 1% loss |
| Temperature Range | -17 to 49_ Celsius |
| Coefficient of Friction | ASTM F1677 / Dry: COF = .65 / Wet: COF = .42, DIN 51130 - R10 |
| Compression Deflection | ASTM D575-91 / 14.15% |
| Tear Strength | Not Available |
| ESD Rating | Not Available |
| Dielectric Strength | Not Available |

| | | | | | | |
|-----|-----|--------|-----------|------------|------------|-----|
| SKU | UPC | Colour | Thickness | Dimensions | Stock Part | UOM |
|-----|-----|--------|-----------|------------|------------|-----|