

24/Seven® LockSafe® MAX Male Edging - Yellow

Group 581.MGRYL



www.wearwell.com

[24/SEVEN® LockSafe® MAX](#) male edging is Grease Resistant and securely interlocks with 24/SEVEN® LockSafe® MAX modular tiles. Yellow edging acts as a visual cue and smooth transition for foot traffic. Grease Resistant rubber (also known as GR or natural rubber) is suitable for dry areas or wet areas where the primary liquid is water.

For use with 24/Seven Locksafe MAX series products only.

- For dry areas or areas with water
- Grease-resistant (Natural Rubber)
- 4 in. x 36 in. (8 cm x 91 cm)
- Overall thickness 1 in (25 mm)
- Also available in [black](#)
- [Corners](#) and [female](#) edging available
- U.S. PATENT No. D882,293 S

| | |
|-----------------------------|-----------------------|
| Wearwell Categories | Anti-Fatigue Flooring |
| Suitable Environment | Dry |
| Customisation Level | C3 |
| Solid or Drainage | Solid |
| Compound | GR/Natural Rubber |
| Recycled | 25% |
| Warranty | 1 Year |

| Property | Test / Result |
|-------------------------|---|
| Flammability | MVSS 302 / 'A'; Rating |
| Taber Abrasion | Federal Standard 191 Modified / 1% loss |
| Temperature Range | 10 to 140 F |
| Coefficient of Friction | ASTM F1677 / Dry: .90 / Wet .020 |
| Compression Deflection | Not Available |
| Tear Strength | Not Available |
| ESD Rating | Not Available |
| Dielectric Strength | Not Available |

| | | | | | | |
|-----|-----|--------|-----------|------------|------------|-----|
| SKU | UPC | Colour | Thickness | Dimensions | Stock Part | UOM |
|-----|-----|--------|-----------|------------|------------|-----|