



www.wearwell.com

## 24/Seven® LockSafe® MAX Corner - Yellow

Group 581.GRYL

**For use with [24/SEVEN® LockSafe® MAX](#) tiles and edging**, these corners connect without cutting or hassle! Grease Resistant rubber (also known as GR or natural rubber) is suitable for dry areas or wet areas where the primary liquid is water.

- For dry areas or areas with water
- Grease-resistant (Natural Rubber)
- 4 in. x 4 in. (8 cm x 9 cm)
- Overall thickness 1 in (25 mm)
- Also available in [black](#)
- [Male](#) and [female](#) edging available
- U.S. PATENT No. D882,293 S

**Wearwell Categories** Anti-Fatigue Flooring

**Suitable Environment** Dry

**Customisation Level** C3

**Solid or Drainage** Solid

**Compound** GR/Natural Rubber

**Recycled** 25%

**Warranty** 1 Year

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	Federal Standard 191 Modified / 1% loss
Temperature Range	10 to 140 F
Coefficient of Friction	ASTM F1677 / Dry: .90 / Wet .020
Compression Deflection	Not Available
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Colour	Thickness	Dimensions	Stock Part	UOM
-----	-----	--------	-----------	------------	------------	-----