



www.wearwell.com

## 24/SEVEN® LockSafe® MAX Diamond-Plate-GR

Group 583-GR

[24/SEVEN® LockSafe® MAX](#) combines the benefits of a modular product with all the comfort of an anti-fatigue mat. Each 3 ft x 3 ft (91cm x 91cm) tile features secure, seamless connections on all sides. The resilient, long-lasting Nitricell sponge base makes 24/SEVEN® LockSafe® MAX the ultimate solution for prolonged standing in areas big and small.

The male and female connectors feature a flange that **lock together and won't come apart until you want them to**. Traditional modular rubber mats have passive connections that fail, leaving dangerous, unsightly trip hazards. 24/Seven MAX saves the time and labor of continual assembly and potential workers' comp claims.

Choose 24/SEVEN® LockSafe® MAX for a dependable, safe, ergonomic floor.

- Diamond-Plate surface pattern
- Large 3 ft x 3 ft tiles (91cm x 91cm)
- Grease Resistant Rubber
- Also available with a [smooth, lightly texture](#) surface
- U.S. PATENT No. D882,293 S

**Wearwell Categories** Anti-Fatigue Flooring

**Suitable Environment** Dry

**Customisation Level** C3 - Full Custom (Length, Width, Shape)

**Solid or Drainage** Solid

**Compound** GR/Natural Rubber

**Recycled** 25%

**Warranty** 1 Year

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	Federal Standard 191 Modified / 1% loss
Temperature Range	10 to 140 F
Coefficient of Friction	ASTM F1677 / Dry: COF = .84 / Wet COF = .45
Compression Deflection	Not Applicable
Tear Strength	Not Applicable
ESD Rating	Not Applicable
Dielectric Strength	Not Applicable

SKU	UPC	Colour	Thickness	Dimensions	Stock Part	UOM
583.1x3x3GRBK	715411014392	Black	1	3' x 3'	Y	EA