



www.wearwell.com

## ErgoDeck General Purpose - Smooth Anti-Fatigue Flooring

### Group 568

Ideal for cart traffic and pivoting, ErgoDeck Smooth™ is a high performance anti-fatigue surface that makes rolling, stopping and starting movements easier than ever. Unlike soft mats that deform under load, ErgoDeck Smooth features a firm, lightly textured surface delivers a smooth surface for rolling but without compromising traction. Optional 6" (15 cm) wide ramps are cart friendly, allowing easy on-off access.

- U.S. PATENT NO. D502,557; D520,650
- Lightly textured surface is ideal for push carts and pivoting
- Customize in 3" (8 cm) increments to fit any area or configuration
- [LockSafe Positive Interlocking System™](#) prevents separation
- Fast installation saves downtime
- Easily replace single pieces or sections as needed to reduce costs
- 100% Silicone Free PVC tiles provide maximum durability
- Overall thickness 7/8" (22 mm)
- Each case covers 22.5 sq. feet (2.2 sq. meters)
- Available in Black or Charcoal

**Wearwell Categories** Anti-Fatigue Flooring

**Suitable Environment** Dry, Wet, Oily

**Customisation Level** C3 - Full Custom (Length, Width, Shape)

**Solid or Drainage** Solid

**Compound** PVC

**Recycled** >80%

**Warranty** Lifetime

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	ASTM D 3884 / 1% loss
Temperature Range	-17 to 49_ Celsius
Coefficient of Friction	ASTM F1677 / Dry: COF = 1.10 / Wet: COF = .91
Compression Deflection	ASTM D575-91 /14.15%
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Colour	Thickness	Dimensions	Stock Part	UOM
568.78x18x18BK	715411698318	Black	0.875	46 x 46	N	EA
568.78x18x18BK-CS10	715411698325	Black	0.875	46 x 46	Y	CS-10
568.78x18x18CH		Charcoal	0.875	46 x 46	N	EA
568.78x18x18CH-CS10		Charcoal	0.875	46 x 46	Y	CS-10