



www.wearwell.com

## WeldSafe®

### Group 447

WeldSafe has a specially formulated SBR rubber surface that repels sparks and hot metal shards. This surface material has a melt point of over 260° Celsius. The Nitrile enhanced Nitricell sponge base absorbs repeated compression and bounces back to its original form better than any PVC sponge alternative. WeldSafe - Accept no substitutes in your critical welding applications!

- "Best" Sponge base
- NFSI Certified
- Machine cut and beveled edges prevent tripping
- Melt point of over 260° Celsius
- Available in 1" (25 mm) and 11/16" (17mm) thick
- **Need a different size?** 1' (30.5cm) incremental lengths are available!

[Simply give us a shout out!](#)

**Wearwell Categories** Mat

**Suitable Environment** Dry

**Customisation Level** C3 - Full Custom (Length, Width, Shape)

**Solid or Drainage** Solid

**Compound** Natural Rubber Surface

**Recycled** >20%

**Warranty** 4 Years

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating.
Taber Abrasion	Federal Standard 191 / 1% lost @ 1,000 cycles
Temperature Range	260 C Melt Point
Coefficient of Friction	ASTM F1677 / Dry: COF = 1.10 / Wet COF = .32
Compression Deflection	ASTM D575 / Deflection @ 35 psi, mm=7.85
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Colour	Thickness	Dimensions	Stock Part	UOM
447.78x2x3BK	715411046416	Black	1"	61 cm x 91 cm	Y	EA
447.78x2x75BK	715411046423	Black	1"	61 cm x 2286 cm	N	RL
447.78x3x5BK	715411046447	Black	1"	91 cm x 152 cm	Y	EA
447.78x3x75BK	715411046454	Black	1"	91 cm x 2286 cm	Y	RL
447.78x4x75BK	715411046478	Black	1"	122 cm x 2286 cm	N	RL
447.916x2x3BK	715411447220	Black	11/16"	61 cm x 91 cm	Y	EA
447.916x2x75BK	715411447213	Black	11/16"	61 cm x 2286 cm	N	RL
447.916x3x5BK	715411447350	Black	11/16"	91 cm x 152 cm	Y	EA
447.916x3x75BK	715411447756	Black	11/16"	91 cm x 2286 cm	Y	RL
447.916x4x75BK	715411447152	Black	11/16"	122 cm x 2286 cm	N	RL

